

Gehl RT250 Compact Track Loader

Yr Built: 2014
MFG: Gehl

Color: Yellow/Black

Price USD \$23,777
SLNC Item #: 20

Comments: Model #: RT250, Serial #: GHLRT250A00070200, Hours 1500 9-24-22



SLNCSurplus4Sale@schuylerline.com

All descriptions given in good faith but without guarantee. – On site inspection available upon appointment.

RT250 GEN:3

TRACK LOADER

GEHL®



KEY FEATURES

- ✓ IdealTrax™ - Automatic Track Tensioning System
- ✓ All-Tach™ Attachment System (Universal-Type)
- ✓ Audible Back-Up Alarm
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Seat Mounted Controls - 4 Choices
- ✓ Auxiliary Hydraulics
- ✓ Entry / Exit Grab Handles

KEY SPECIFICATIONS

- ✓ Operating capacity (35%) – 1134 kg (2,500 lbs.)
- ✓ Overall height to top of ROPS – 2111 mm (83.1")
- ✓ Gross Power – 55.4 kW (74.3 hp) @ 2300 rpm
- ✓ Deutz / TD 3.6 / Tier IV / Stage 3B
- ✓ 330.3 Nm (243 ft.-lbs.) @ 1700 rpm max torque
- ✓ 3251 mm (128") height to hinge pin
- ✓ 1765 mm (69.5") machine width - less bucket
- ✓ 5260 kg (11,600 lbs.) operating weight

RT250 GEN:3 TRACK LOADER

SPECIFICATIONS

	IMPERIAL	METRIC		
DIMENSIONS	Overall Operating Height - Fully Raised	168"	4267 mm	
	Height to Hinge Pin - Fully Raised	128"	3251 mm	
	Dump Reach at Full Height	34.5"	876 mm	
	Dump Angle at Full Height		41°	
	Dump Height - Fully Raised	98"	2489 mm	
	Rollback Angle at Full Height		102.5°	
	Overall Height to Top of ROPS	83.1"	2111 mm	
	Overall Length with Bucket (w/o Counterweight)	157.8"	4008 mm	
	Overall Length without Bucket (w/o Counterweight)	126.8"	3221 mm	
	Specified Height	67.7"	1720 mm	
	Reach at Specified Height	31.3"	795 mm	
	Dump Angle at Specified Height		75°	
	Maximum Rollback Angle at Ground		30°	
	Carry Position	8.2"	208 mm	
	Maximum Rollback Angle at Carry Position		31.6°	
	Digging Position – Above Ground	+0.5"	13 mm	
	Angle of Departure (w/o Counterweight)		25°	
	Ground Clearance to Chassis	13.2"	335 mm	
	Track Gauge	51.7"	1313 mm	
	Track Shoe Width	17.7"	450 mm	
	Crawler Base	61.5"	1562 mm	
	Overall Width - Less Bucket	69.5"	1765 mm	
	Bucket Width	83.9"	2131 mm	
	Clearance Radius – Front with Bucket	98.4"	2499 mm	
	Clearance Radius – Rear (w/o Counterweight)	70.7"	1796 mm	
	Maximum Rollback at Specified Height		66.8°	
	Angle of Approach		90°	
	Grouser Height	1"	25 mm	
	CAPACITY	Operating Capacity at 35% Tipping Load	2,500 lbs.	1134 kg
		Operating Capacity at 50% Tipping Load	3,571 lbs.	1620 kg
Tipping Load		7,143 lbs.	3240 kg	
Operating Weight		11,600 lbs.	5260 kg	
ENGINE	Make/Model	Deutz / TD 3.6 / Tier IV / Stage 3B		
	Displacement/Cylinders	221 cu. in./4	3.6 L/4	
	Gross Power @ 2300 rpm	74.3 hp	55.4 kW	
	Net Power @ 2300 rpm	70.7 hp	52.7 kW	
	Peak Torque @ 1500 rpm	243 ft-lbs	330 Nm	
	Oil Pan Capacity	9 qts.	8.5 L	
	Alternator Voltage / Amperage	14 V / 95 A		
TRACK DRIVES	Drawbar Pull / Tractive Effort	12,770 lbs.	5792 kg	
	Track Type / Track Rollers / Roller Type	Rubber / 5 / Steel		
	Track Width	17.7"	450 mm	
	Ground Pressure	5.3 psi	0.37 bar	
FORCES	Bucket Breakout - Tilt Cylinder	8,384 lbs.	3803 kg	
	Bucket Breakout - Lift Cylinder	7,437 lbs.	3373 kg	
	Ground Speed – Single Speed	5.8 mph	9.3 km/h	
	Ground Speed – Two Speed	8.2 mph	13.2	
VOLUME	Fuel Tank	24 gal.	91 L	
	Hydraulic Reservoir Tank	13.8 gal.	52.2 L	
	Coolant Capacity	6.1 gal.	23.1 L	
HYDRAULICS	Auxiliary Hydraulic Flow - Rated Speed	24.9 gpm	94.3 L/min	
	High-Flow Hydraulic Flow - Rated Speed	37.4 gpm	141.6 L/min	
	Transmission Pump Type	Axial Piston		
	Motor Type	Axial Piston w/ Planetary Gear Box Reduction		
BATTERY	Battery Volts	12 V		
	Cold Cranking Amps at @ 0° F (-18° C)	950 CCA		

STANDARD FEATURES

- Joystick Control w/ Variable Drive
- Fuel Gauge
- Battery Charge Indicator Lamp
- Low Oil Pressure Light and Buzzer
- Seatbelt Indicator Lamp and Buzzer
- Coolant Temperature Gauge
- Hourmeter
- Manual-Control Hydrostatic Drive
- All-Tach™ Attachment System (Universal-Style)
- IdealTrax™ - Automatic Track Tensioning System
- ROPS/FOPS- Level II – Approved Overhead Guard
- Direct Drive Tandem Hydrostatic Pumps, High-Gain Servo Controlled
- Drive Sensitivity Adjustment - 5 Selectable Drivability / Responsiveness Settings
- Warning Lamps and Buzzer – Engine and Hydraulic Oil Temperature
- Operator Restraint Bar with Armrests
- Independent Hydraulic Reservoir and Hydraulic Oil Cooler
- Audible Back-Up Alarm
- Engine Intake Air Pre-Heater Starting Assist
- Adjustable Seatbelt
- Lift Arm Support Device
- Hydraloc™ System
- Dual Front and Rear Work Lights
- Removable Belly Plate and Access Cover
- Dual-Element Air Cleaner with Visual Indicator
- Vandalism Lock Provisions
- Top and Rear Windows
- Headliner and Acoustical Interior
- Deluxe High Back, Cushion Seat
- Front Auxiliary Hydraulics with 3/4-inch Flat-Faced Couplers
- Visual Hydraulic Filter Indicator
- Power Plug (12 V)
- Sound Reduction Package
- Horn



OPTIONAL FEATURES

- Power-A-Tach® - Electrically Powered Quick-Attach System
- Rear Camera - Includes 5" (127 mm) Display
- Engine Block Heater
- Suspension Seat
- Cab Door with Wiper and Dome Light
- Sliding Side Windows
- Heater/Defroster
- Deluxe Sound Package
- 3-inch Wide Seatbelt – When Required by Law
- Rear View Mirror
- Engine Auto-Shutdown System
- Interior Dome Light
- Centrifugal Pre-Cleaner
- Strobe Light
- Impact-Resistant Door
- Four-Point Lift Kit
- Rear Counterweight
- Bucket Bolt-On Cutting Edge
- Self-Leveling Lift Action
- Easy Manager Telematics
- Battery Disconnect Switch



geh.com

One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.